

PIKA Lite- LoRaWAN Modbus Specifications

Version: V1.1 – October 2025



Overview

IoT device PIKA is an easy and intelligent device dedicated to collecting data from on-site Modbus RTU / Modbus TCP devices, and transmitting them to the Internet via LoRaWAN. It can read up to 50 Modbus register addresses on 8 Modbus devices with the same configuration. The feature supports importing and exporting Modbus registers files to CSV format, allowing users to easily manage effectively.

Specifications

Category

Specification

Wireless Transmission

LoRaWAN
Frequency: EU433, CN470, IN865,
EU868, AU915, US915, KR920, RU864,
AS923-1/2/3/4 (default AS923-2)
Tx Power: 16dBm (923 MHz)
Sensitivity: -137 dBm

Modbus Interface

Modbus RTU (Terminal Block 3.81mm
connector, 1200–115200bps)
Modbus TCP/IP (RJ45, optional)

Data Configuration

Port: Type-C
Tool: WNE PC Tool Software

Physical Characteristics

Power: 6–24VDC (<5W)
Connector: Terminal Block 3.81mm
Material: PC+ABS, White
Ingress Protection: IP54
Operating Temp: -20°C~60°C
Humidity: 0–95% RH
Dimensions: 124×67×34 mm
Installation: Wall mounting

Others

User Button : Run/Stop Mode
Reset Button: Internal
Lora Antenna: 3dBi

Software Features

PIKA Lite is configured via the COM port using the WNE Tool software, which allows setting up all device parameters and features :

- [Status Tab](#) – Display device status information.
- [LoRaWAN Setting](#) – regional band, class (A/C), join mode (OTAA/ABP), device & network identifiers, session keys, application port, data rate, transmit power, ADR, and retry options.
- [Modbus Setting](#) – Configure Modbus RTU/TCP parameters, register tables, CSV import/export, connection test.
- [Pulse Setting](#) – For pulse counter option.
- [Pressure Setting](#) – For pressure sensor option.
- [Basic Setting](#) – Configure Device ID, reporting interval, and password.
- [Serial Log](#) – Enable/disable serial port logging.
- [Run/Stop](#) – For Run/Stop mode option

PIKA Lite supports the following LoRaWAN Downlink Commands including:

- [Change Reporting Interval](#).
- [Send an Immediate Report \(Class C\)](#).

Package Inclusions

1. 1 pc PIKA Lite
2. 1 pc 12V/1A Power Adapter (optional)
3. 1 pc Lora Antenna
4. 1 Type-C USB cable
5. 1 pc Terminal Block 3.81mm 6P

Documentation

PIKA Lite User Manual